



US009410437B2

(12) **United States Patent**  
**Paige et al.**

(10) **Patent No.:** **US 9,410,437 B2**  
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **AIRFOIL COMPONENTS CONTAINING  
CERAMIC-BASED MATERIALS AND  
PROCESSES THEREFOR**

(71) Applicant: **General Electric Company**,  
Schenectady, NY (US)

(72) Inventors: **Anthony Reid Paige**, Jupiter, FL (US);  
**Mark Eugene Noe**, Morrow, OH (US);  
**Michael James Verrilli**, Loveland, OH  
(US); **Mark Willard Marusko**,  
Springboro, OH (US); **Joshua Brian  
Jamison**, Liberty Township, OH (US);  
**Paul Izon**, Morrow, OH (US)

(73) Assignee: **General Electric Company**,  
Schenectady, NY (US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 152 days.

(21) Appl. No.: **13/721,349**

(22) Filed: **Dec. 20, 2012**

(65) **Prior Publication Data**

US 2014/0050893 A1 Feb. 20, 2014

**Related U.S. Application Data**

(60) Provisional application No. 61/682,870, filed on Aug.  
14, 2012.

(51) **Int. Cl.**  
**F01D 5/18** (2006.01)  
**F01D 5/28** (2006.01)  
**F01D 5/20** (2006.01)

(52) **U.S. Cl.**  
CPC .. **F01D 5/28** (2013.01); **F01D 5/20** (2013.01);  
**F01D 5/284** (2013.01); **F01D 5/187** (2013.01);  
(Continued)

(58) **Field of Classification Search**  
CPC ..... F01D 5/18; F01D 5/20; F01D 5/284  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

5,015,540 A 5/1991 Borom et al.  
5,330,854 A 7/1994 Singh et al.

(Continued)

**FOREIGN PATENT DOCUMENTS**

CN 1926250 A 3/2007  
CN 101131099 A 2/2008

(Continued)

**OTHER PUBLICATIONS**

PCT Search Report and Written Opinion issued May 12, 2014 in  
connection with corresponding PCT Patent Application No. PCT/  
US2013/050847.

(Continued)

*Primary Examiner* — Scott W Dodds

(74) *Attorney, Agent, or Firm* — General Electric Company;  
Brian P. Overbeck

(57) **ABSTRACT**

A process for producing airfoil components containing ceramic-based materials and having a tip cap. The process entails forming an airfoil portion of the component from an airfoil portion material that contains a precursor of a ceramic-based material. The airfoil portion material defines concave and convex walls of the airfoil portion, and the concave and convex walls define a tip region of the airfoil portion and at least one cavity within the airfoil portion. At least a first ply is formed that contains a precursor of a ceramic-based material, and the first ply at least partially closes the cavity at the tip region of the airfoil portion. The airfoil portion material and the first ply are then cured so that the first ply forms a tip cap that closes the cavity and the precursors of the airfoil portion material and first ply are converted to the ceramic-based materials thereof.

**20 Claims, 5 Drawing Sheets**

